



WINCH BST S 4500 LBS



Technical specifications

| | |
|-----------------------------|---------------------------------|
| Pull capacity (single line) | 4500 lbs/ 2041 Kg |
| Motor | 1, 8 HP / 1,3 kW |
| Controls | wired / wireless remote control |
| Gear | 3 - stage planetary |
| Gear ratio | 198:1 |
| Brake | automatic friction brake |
| Rope | 12 m x ø 5,5 mm |
| Net weight | 6 Kg |
| Dimensions L x W x H | 322 mm x 114 mm x 115, 5 mm |
| Fairlead | aluminium hawse |
| Mounting bolt pattern | 124 mm x 76 mm |

Included :

- hook
- synthetic rope
- hawse fairlead
- mounting plate
- mounting screws
- wired remote control
- wireless remote control
- control set

Line speed and motor (first layer)

| | | | | | | |
|---------------|------------|-----|------|------|------|------|
| Line pull | Lbs | 0 | 1000 | 2000 | 3000 | 4500 |
| | Kg | 0 | 454 | 907 | 1360 | 2041 |
| Line speed | M/min 12 V | 4,9 | 3,2 | 2,8 | 2,2 | 1,4 |
| Motor current | Amper 12 V | 17 | 70 | 105 | 135 | 180 |

Line pull and cable capacity

| | | | | | |
|-----------------|-----|------|------|------|------|
| Layer of cable | | 1 | 2 | 3 | 4 |
| Rated line pull | Lbs | 4500 | 3841 | 3310 | 2907 |
| per layer | Kg | 2041 | 1742 | 1501 | 1319 |
| Cable capacity | M | 2 | 4,3 | 7,2 | 12 |
| per layer | | | | | |