



WINCH BST 13000 LBS

IP67

Technical specifications

Pull capacity (single line)	13000 lbs / 5897 Kg
Motor	6,5 HP / 4,7 kW 8,5 HP / 6,2 kW
Controls	wired / wireless remote control
Gear	3 - stage planetary
Gear ratio	265:1
Brake	automatic friction brake
Rope	26 m x ø 10 mm
Net weight	20 Kg
Dimensions L x W x H	535 mm x 160 mm x 218 mm
Fairlead	aluminium hawse
Mounting bolt pattern	254 mm x 114,3 mm 4-M12

Included :

- hook
- synthetic rope
- hawse fairlead
- mounting screws
- wired remote cotrol
- wireless remote control
- control set

Line speed and motor (first layer)

Line pull	Lbs	0	4000	6000	10000	13000
	Kg	0	1814	2722	4536	5897
Line speed	M/min 12 V	6,8	3,8	3	2,1	1,7
	M/min 24 V	10	7	5,5	3,2	2,7
Motor current	Amper 12 V	80	170	210	310	380
	Amper 24 V	45	70	95	185	250

Line pull and cable capacity

Layer of cable		1	2	3	4
Rated line pull	Lbs	13000	9900	8300	7000
per layer	Kg	5897	4490	3765	3175
Cable capacity	M	6	13	22	25
per layer					