



WINCH BST S 18000 LBS

IP67

Technical specifications

Pull capacity (single line)	18000 lbs / 8165 kg
Motor	5,5 HP / 4,0 kW 7,5 HP / 5,5 kW
Controls	wired / wireless remote control
Gear	3 - stage planetary
Gear ratio	450:1
Brake	automatic friction brake
Rope	30 m x ø 11 mm
Net weight	70 kg
Dimensions L x W x H	593 mm x 226 mm x 254 mm
Fairlead	4-ways rolles
Mounting bolt pattern	254 mm x 114,3 mm 4-M12

Included :

- hook
- steel rope
- roller fairlead
- mounting screws
- wired remote control
- wireless remote control
- control set

Line speed and motor (first layer)

Line pull	Lbs	0	10000	12000	15000	18000
	Kg	0	4536	5443	6804	8165
Line speed	M/min 12 V	4,6	1,7	1,9	1,37	1,2
	M/min 24 V	4,9	2,2	2,1	1,8	1,7
Motor current	Amper 12 V	90	285	260	340	410
	Amper 24 V	48	140	145	191	235

Line pull and cable capacity

Layer of cable		1	2	3	4
Rated line pull	Lbs	18000	12000	10100	8720
per layer	Kg	8165	5443	4581	3955
Cable capacity	M	6	13	21	30
per layer					