



WINCH BST V 12000 LBS

IP68

Technical specifications

Pull capacity (single line)	12000 lbs / 5443 Kg
Motor	6,6 HP / 4,9 kW, 12 V DC
Controls	wired / wireless remote control
Gear	3 - stage planetary
Gear ratio	216:1
Brake	automatic friction brake
Rope	26 m x ø 10 mm
Net weight	24 Kg
Dimensions L x W x H	563 mm x 160 mm x 280 mm
Fairlead	aluminium hawse
Mounting bolt pattern	254 mm x 114,3 mm 4-M12



Recommended for:
Off- road



LED lights

Included :

- hook
- synthetic rope
- hawse fairlead
- mounting screws
- wired remote control
- wireless remote control
- control set
- switch on the control
- line illumination

Line speed and motor (first layer)

Line pull	Lbs	0	4000	6000	9500	12000
	Kg	0	1814	2722	4309	5443
Line speed	M/min 12 V	10	4,6	4	3,2	2,8
Motor current	Amper 12 V	70	210	260	380	420

Line pull and cable capacity

Layer of cable		1	2	3	4
Rated line pull	Lbs	12000	9919	8221	7019
per layer	Kg	5443	4499	3729	3183
Cable capacity	M	4,8	10	18,1	26
per layer					