



WINCH BST S 14000 LBS



Technical specifications

Pull capacity (single line)	14000 lbs / 6350 Kg
Motor	6,4 HP / 4,7 kW 6,7 HP / 4,9 kW
Controls	wired / wireless remote control
Gear	3 - stage planetary
Gear ratio	332:1
Brake	automatic friction brake
Rope	28 m x ø 10 mm
Net weight	41 Kg
Dimensions L x W x H	573 mm x 206 mm x 249 mm
Fairlead	aluminium hawse
Mounting bolt pattern	254 mm x 114,3 mm 4-M12

Included :

- hook
- synthetic rope
- hawse fairlead
- mounting screws
- wired remote control
- wireless remote control
- control set
- battery isolation switch

Line speed and motor (first layer)

Line pull	Lbs	0	8000	10000	14000
	Kg	0	3629	4536	6350
Line speed	M/min 12 V	5	1,9	1,7	1,2
	M/min 24 V	5,4	2	1,8	1,5
Motor current	Amper 12 V	80	310	350	480
	Amper 24 V	40	145	185	250

Line pull and cable capacity

Layer of cable		1	2	3	4
Rated line pull	Lbs	14000	11255	9410	8085
per layer	Kg	6350	5105	4268	3667
Cable capacity	M	5,6	12,5	20	28
per layer					