



WINCH BST RS 12000 LBS TWIN MOTOR



Recommended for:
Off- road

Technical specifications

Pull capacity (single line)	12000 lbs/5443 kg
Motor	twin motors 7.2 HP/5.4 Kw/12 V DC
Controls	wired/wireless remote control
Gear	3 - stage planetary
Gear ratio	81:1
Brake	external disc brake with ratchet
Rope	50 m x ø 10 mm
Net weight	78,5 kg
Dimensions L x W x H	510 mm x 288 mm x 395 mm
Fairlead	aluminium hawse
Mounting bolt pattern	329 mm x 114,3 mm 6-M12
Max pressure	0,8 Mpa

Included :

- hook
- synthetic rope
- hawse fairlead
- mounting screws
- wired remote control
- wireless remote control
- control set
- electrovalve

Line speed and motor (first layer)

Line pull	lbs	0	5000	8000	12000
	kg	0	2268	3629	5443
Line speed	m/min 12 V	25	7,2	5,4	4,5
		Motor current	100	350	465
	amper 12 V				

Line pull and cable capacity

Layer of cable Rated line pull per layer	lbs kg	1	2	3	4	5
		12000 5443	9176 4162	7428 3369	6240 2830	5379 2439
Cable capacity per layer	m	5	11,7	20	29,5	40